

Area of Application:

Table mounted  
Water

Max. working pressure 10 bar  
Temperature range 5°C-65°C

Details:

Servo controlled bi-stable cartridge valve  
Swivel limited 110°  
Aerator M22x1

Materials in media contact:

Brass  
Rubber, EPDM  
Silicone based lubricant  
PPSU  
SS  
PA  
SPX Hose

Mounting:

M30x1,5 nut with locking pins o-ring and washer (See 94G0232)

Inlet / outlet connection:

Union Nut G1/2"  
Aerator M22x1

Electronic connection:

100-240 V AC 50/60 Hz

Infrared sensor

Ø 30

Standard hose length 500mm

Cable length 300mm

Power plug for EU  
Cable length 1100mm

200

300

212

60

Aerator with 5L/min flowfix

M5 screws not included

ISO 1/2"

Description: 1-Valve, Table mounted, 1-Hole, Swivel limited 110°, M30x1,5mm

Media: Water

Comments:

Drawing type: Customer drawing

Weight: 1.489 Kg

Rev. Pos. Date TM No. Design by Drawn by: Change:

Designed by: REK Drawn by: REK Released on TM No. Date: 29-04-2019

**BROEN-LAB**

This drawing is our property and cannot be given to a third party, copied or otherwise used without our permission. BROEN-LAB A/S.

Format: A3 Drawing No.: 26010171035-52E